


MATERIAL SAFETY DATA SHEET

NFPA Designation 704
DEGREE OF HAZARD
4 = EXTREME
3 = HIGH
2 = MODERATE
1 = SLIGHT
0 = INSIGNIFICANT



May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910, 1200. Standard must be consulted for specific requirements.

U.S. DEPARTMENT OF LABOR Occupational Safety and Health Administration (Non-Mandatory Form) Form-Approved OMB No. 1218.0072

CHEMICAL NAME

Fabriccover® Gold

PRODUCT USAGE

Fabric Protector For Carpeting

SECTION I

Manufactured For:	Steam Way® International	Emergency Telephone Number:	(303) 355-3566
Address:	4550 Jackson Street	Telephone Number For Information:	(303) 355-3566
City, State, Zip	Denver, Colorado 80216	Date Prepared:	April 9, 1993 Updated: July 1, 1999

SECTION II - Hazardous Ingredient Information

Hazardous Components (If component is non-hazardous, specify by * designation) (Specific Chemical Identity: CAS#)	% optional
*NJ Trade Secret Registry #00850201001-5155P	5 - 15%
*NJ Trade Secret Registry #008500201001-5259P	0.5 - 2%
*Polymethylmethacrylate CAS# 9011-14-7	1-5%
*NJ Trade Secret Registry #008500201001-5402P	0 - 3%
*NJ Trade Secret Registry #008500201001-5403P	0 - 3%
*Citric Acid CAS# 77-92-9	2 - 4 %
*Water CAS# 7732-18-5	70 - 90%

SECTION III - Physical/Chemical Characteristics

Boiling Point	212°F (100°C)	Specific Gravity (H ₂ O = 1)	1.03
Vapor Pressure (mm Hg.)	unknown	Melting Point	None
Vapor Density (Air=1)	unknown	Evaporation Rate (Butyl Acetate=1)	Slower than ether
Solubility Rate	complete	Percent. Volatile by Volume (%)	70 WT %

Appearance and Odor Aromatic liquid, light yellow-red.

SECTION IV - Fire and Explosion

Flash Point (Method Used)	N.A.	Flammable Limits	UEL N.I.	LEL N.I.
---------------------------	------	------------------	----------	----------

Extinguishing Media Use media appropriate for surrounding material.

Special Fire Fighting Procedures Keep personnel removed and upwind of fire. Wear self-contained breathing apparatus. Wear full protective equipment.

Unusual Explosion Hazard In fire conditions, toxic decomposition products may be formed. These products may cause eye, nose, throat and lung irritation.

SECTION V - Reactivity Data

Stability Stable at normal temperatures and storage conditions	Unstable		Conditions to Avoid
	Stable	X	

Incompatibility (Materials to Avoid) Incompatible with mineral acids (precipitates).

Hazardous Decomposition or by-Products Heating above 392°F (200°C) toxic decomposition products may be formed. These products may cause eye, nose, throat, and lung irritation.

<u>Hazardous Polymerization</u>	May Occur		Conditions to Avoid
	Will Not Occur	X	

SECTION VI - Health Hazard Data

Health Hazards (Acute and Chronic): Route(s) of Entry/Signs and Symptoms of Exposure

Avoid prolonged skin contact. Avoid eye contact. Use only with adequate ventilation. Do not take internally.

Emergency and First Aid Procedures

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician. If skin contact, flush with water. Wash contaminated clothing before reuse. For eye contact, immediately flush with plenty of water for at least 15 minutes. If irritation persists, Call a physician. If swallowed, do not induce vomiting. Immediately give two glasses of water. Never give anything by mouth to an unconscious person. Contact a physician.

Carcinogenicity: NIP? IARC Monographs? OSHA Regulated?

None

Medical Conditions Generally Aggravated by Exposure

See health hazards above.

SECTION VII - Precautions For Safe Handling And Use

Steps To Be Taken In Case Material is Released or Spilled REVIEW FIRE AND EXPLOSION HAZARDS AND SAFETY PRECAUTIONS before proceeding with clean up. Use appropriate personal protective equipment during clean up. Prevent liquid from entering sewers, waterways or low areas. Soak up with sawdust, sand, oil dry or other absorbent material. Shovel or sweep up.

Waste Disposal Method

Dispose of in accordance with all federal, state, and local regulations.

Precautions To Be Taken In Handling And Storing

Keep container tightly closed. Keep from freezing.

Other Precautions

Do not take internally or inhale vapors. Avoid eye contact. Keep container closed when not in use. Do not aerosolize. In spray applications, use airless type pressure spray equipment at less than 60 P.S.I. Use only with adequate ventilation to avoid inhalation of respirable particle. Keep away from open flames and heated surfaces above 392°F (200°C). Toxic decomposition products may be formed which may cause eye, nose, throat, and lung irritation.

SECTION VIII - Control Measures

Respiratory Protection (Specific Type)

NIOSH approved cartridge respirator for high vapor concentrations.

<u>Ventilation</u>	<u>Local Exhaust</u> As needed to keep concentrations below acceptable levels.	<u>Special</u>
	<u>Mechanical (General)</u>	<u>Other</u>

Protection Gloves

Impermeable gloves

Eye Protection

Chemical safety goggles

Other Protective Clothing or Equipment

Usually not needed unless splashing is excessive.

Work/Hygienic Practices

Observe personal hygiene