



## SECTION V - Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable	X	When heated, emits toxic fumes

### Incompatibility (Materials to Avoid)

Strong oxidizers, acids, silver compounds, acrolein, dimety sulfate, halogens, or anything reactive with water.

### Hazardous Decomposition or by-Products

Ammonia fumes, carbon monoxide and smoke.

Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	

## SECTION VI - Health Hazard Data

### Health Hazards (Acute and Chronic): Rout(s) of Entry/Signs and Symptoms of Exposure

Routes of entry are skin, inhalation and ingestion. Contact with eyes or skin will be painful and irritating. Toxic by ingestion. Avoid inhalation over TLV for ammonia - Toxic by inhalation.

### Emergency and First Aid Procedures

Flush eyes thoroughly with plenty of water for at least 15 minutes. Flush off skin with plenty of water. If vapors cause discomfort, remove to fresh air, give artificial respiration if breathing has stopped and call a physician immediately. If ingested, get immediate attention. DO NOT INDUCE VOMITING. Give conscious patient large quantities of water.

Carcinogenicity: NIP? IARC Monographs? OSHA Regulated?

### Medical Conditions Generally Aggravated by Exposure

See health hazards above.

## SECTION VII - Precautions For Safe Handling And Use

### Steps to be taken in Case Material is Released or Spilled

Flush way with water or soak up with sand or sweeping compound and shovel into waste containers.

### Waste Disposal Method

Bury or flush to sewage disposal system in accordance with all federal, state, and local regulations.

### Precautions To Be Taken In Handling And Storing

Storage in a cool dry place between 40°F and 100°F is recommended. Keep away from sources of ignition separate from oxidizing agents, chlorine, bromine, iodine, and acids.

### Other Precautions

Do not take internally or inhale vapors. Avoid eye contact.

## SECTION VIII - Control Measures

### Respiratory Protection (Specific Type)

Use NIOSH approved respirator when mists are above TLV for ammonia, amyl acetate or isopropyl alcohol.

Ventilation	Local Exhaust	Special
	Mechanical (General)	Other
	Acceptable	

### Protection Gloves

Rubber gloves

### Eye Protection

Chemical safety goggles

### Other Protective Clothing or Equipment

Usually not needed unless splashing is excessive.

### Work/Hygienic Practices

To the best of our knowledge, the information contained herein is accurate. However, neither Steam Way® International, Inc. its suppliers, nor its distributors assumes any liability whatsoever for the accuracy or completeness of the information. Final determination of the suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards may be described herein, we cannot guarantee that these are the only hazards which exist. Information herein is given in good faith, but no warranty, expressed or implied, is made.