



GREENER SOLUTIONS

Carpet & Upholstery Cleaner



WHAT IS CARPET & UPHOLSTERY CLEANER?

Provides excellent cleaning results on heavy grease, oil & dirt soiled carpets and upholstery. It will remove the ground-in dirt from severely soiled traffic lanes. It will also remove tough spots and stains caused by blood, various inks, road tar, ketchup, shoe polish, tea, coffee, food and beverage residues, and more!

BENEFITS:

- Safe for use on most stone surfaces
- No Toxic or Hazardous
- Removes protein stains
- Removes Soil Build-up
- No colors or fragrances added
- Can be used with hot and cold water
- User Safe

DIRECTIONS FOR USE:

Before using, make sure that the desired surface is cool to prevent early evaporation. Read MSDS and test in a small inconspicuous area. Dispose of unused materials in a landfill in accordance with all local, state and federal regulations.

Using more is NOT better. Use as directed.

PRE-SPRAY/EXTRACTION: For use on heavily soiled carpet traffic areas. Effectively dissolves grease, dirt, grime, spots and stains. Mix 4 oz. to 1 gallon of COLD, WARM or HOT water. Pre-spray evenly. DO NOT OVER WET. Let dwell for 10 minutes. Extract with fresh water.

PORTABLE EXTRACTION (without pre-spray): Mix 2 oz. to 1 gallon of COLD, WARM or HOT water. For all portable extractors including extractors with a siphon tube. In this case, simply place the siphon tube into the concentrated liquid.

BONNET CLEANING: Mix 4 oz. to 1 gallon of COLD, WARM or HOT water. Pre-spray evenly on heavily soiled area. Let dwell for 10 minutes. For best results, bonnet using 100% cotton bonnet pads.

WICKING & BROWNING: Mix 2 oz. to 1 gallon of COLD, WARM or HOT water. Pre-spray the carpet fiber. DO NOT OVER WET. Let dwell for 10 minutes. For best results bonnet using 100% cotton bonnet pads to absorb moisture and to prevent wicking or browning problems.

UPHOLSTERY: Mix 2 oz. to 1 gallon of COLD or WARM water. Pre-spray evenly, applying from the base of the upholstery going up and extract from the top going down.

HYDRO FORCE: Mix 32 oz. to 1 gallon of WARM or HOT water (meter 1:8). Apply evenly. Let dwell for 10 minutes.

TRUCK MOUNT: Fresh water rinse. Set heat at 180° to 200° NOTE: Rinsing agents are not needed.

PERSONAL PROTECTIVE EQUIPMENT: When mixing or handling product, use chemical glasses and protective gloves.

GREENER SOLUTIONS

24 Victory Lane, Dracut, MA 01826

For more information visit us online @ www.syntecpro.com or www.newenglandsteamway.com

Tech Specs:

Color.....Clear
 Odor.....No fragrance added
 pH.....9.5
 Form.....Liquid
 Biodegradable.....100%